



Taflon®

Bring Leader on the Floor

PRO S1

New construction TILE ADHESIVE

Premium
Superior
Creamy

- Ideal for fixing Small format Tiles on floor and wall on interior areas.
- Economical & easy to use.
- Tile application on the wall which have no Primer
- Excellent adhesion & low Shrinkage.
- Company is not responsible for any wrong application.



EASY TO APPLY



USE NOTCH TROWEL



EXCELLENT
COVERAGE

CONTENTS
20 Kg.



Green India
More Green More Wealth

Excellent bond strength
High grab and non sag

Can be used extreme
conditions

Single component just
add water
Saves time & increases
productivity.

High strength formula
and ultimate flexibility





Taflon[®]

Bring Leader on the Floor

ECO S2

POLYMER MODIFIED TILE ADHESIVE

- Ideal for fixing Ceramic tiles on Interior and Extranal areas.
- Ideal for fixing small format vitrified tiles on interior wall and floor.
- Excellent adhesion & low Shrinkage.
- Economical & easy to use.
- Tile applicaton on the wall which have no Primer
- Company is not responsible for any wrong application

Premium
Superior
Creamy



EASY TO APPLY



USE NOTCH TROWEL



EXCELLENT
COVERAGE

CONTENTS
20 Kg.



Green India
Bharat Shiksha Disha

Excellent bond strength
High grab and non sag

Can be used extreme
conditions

Single component just
add water
Saves time & increases
productivity

High strength formula
and ultimate flexibility





Taflon[®]

Bring Leader on the Floor

BIO S3

HIGH PERFORMANCE POLYMER BASED TILE ADHESIVE

Premium
Superior
Creamy



EASY TO APPLY



USE NOTCH TROWEL



EXCELLENT
COVERAGE

CONTENTS
20 Kg.

- Ideal for fixing medium format vitrified tiles on Interior as well as Extrnal areas.
- Tile on tile application on Interior floor areas.
- Cladding application on Interior and extrnal Surface.
- Excellent adhesion & low Shrinkage.
- Economical & easy to use.
- Tile application on the wall which have no Primer
- Company is not responsible for any wrong application



Green India
Bharat Bhava Bharat

Excellent bond strength
High grab and non sag

Can be used extreme
conditions

Single component just
add water
Saves time & increases
productivity.

High strength formula
and ultimate flexibility





Taflon®

Bring Leader on the Floor

GEL S4

MULTIPURPOSE
HIGH POLYMER WITH GEL MODIFIED
TILE ADHESIVE

- Specially Design For Outdoor, Front Elivation & Open Area
- Large Format Ceramic vitrified body on Interior wall as well as Extranal areas.
- Glass mosalcs, swimming pools, Tile on tile application on all extranal Surface.
- Natural stone clading, tiles slabs application.
- Excellent adhesion & low Shrinkage.
- Economical & easy to use.
- Tile application on the wall which have no Primer
- Company is not responsible for any wrong application

Premium
Superior
Creamy



EASY TO APPLY



USE NOTCH TROWEL



EXCELLENT
COVERAGE

CONTENTS
20 Kg.



Green India
Rise With Growth

Excellent bond strength
High grab and non sag

Can be used extreme
conditions

Single component just
add water
Saves time & increases
productivity.

High strength formula
and ultimate flexibility





HIGH PERFORMANCE GEL EPOXY GROUT

Taflon[®]

Bring Leader on the Floor

GEL EPOXY GROUT Gel



HIGH PERFORMANCE Two Component EPOXY GROUT

Specially Design For Outdoor, Front Elevation & Terrace Open Area

Premium Superior Creamy

Suitable substrates:

- Concrete
- Brick masonry
- Concrete masonry
- Cement mortar beds
- Asphalt wallboard
- Ceramic tile and stones
- Exterior glue plywood
- Non-water soluble cut-back adhesive
- Vinyl or other resilient tile
- Plastic laminate
- Cement backer board
- Steel/Cement plaster
- Cement terrazzo









5Kg
Net Wt.



HIGH PERFORMANCE GEL EPOXY GROUT

NEED USE TOOLS

Clean Cloth
Trowel
Spatula

Temperature

Apply temperature in the range of 10°C to 30°C. If the temperature is below 10°C, the product will not cure properly. If the temperature is above 30°C, the product will cure too fast and may crack.

Precautions:

Wear protective gear (gloves, goggles, mask) when handling the product. Avoid contact with skin and eyes. If contact occurs, wash immediately with water. Do not inhale the dust. Store in a cool, dry place.

Substrate	Ratio (Part A : Part B)	Application Method	Curing Time (at 25°C)
Concrete	1 : 1	Hand-applied	24 hours
Brick masonry	1 : 1	Hand-applied	24 hours
Concrete masonry	1 : 1	Hand-applied	24 hours
Cement mortar beds	1 : 1	Hand-applied	24 hours
Asphalt wallboard	1 : 1	Hand-applied	24 hours
Ceramic tile and stones	1 : 1	Hand-applied	24 hours
Exterior glue plywood	1 : 1	Hand-applied	24 hours
Non-water soluble cut-back adhesive	1 : 1	Hand-applied	24 hours
Vinyl or other resilient tile	1 : 1	Hand-applied	24 hours
Plastic laminate	1 : 1	Hand-applied	24 hours
Cement backer board	1 : 1	Hand-applied	24 hours
Steel/Cement plaster	1 : 1	Hand-applied	24 hours
Cement terrazzo	1 : 1	Hand-applied	24 hours


Taflon
EPOXY GROUT



Taflon[®]

Bring Leader on the Floor

PU Adhesive

**FIXES TILES
& STONES**

MULTI SURFACE FLEXIBLE ADHESIVE

**DESIGNED FOR METAL, PLYWOOD
& OTHER DRYWALL APPLICATION**



Taflon®

Bring Leader on the Floor

An Iso 9001: 2015 Certified Company

PIXEL

ECO WD7

2 PART EPOXY GROUT

PART A+B

EASY TO APPLY
EASY TO CLEAN



15kg

© **TAFLON**
GEL S10
RESIN
ADHESIVE

תאפלוניזציה

התהליך של תאפלוניזציה הוא תהליך כימי שבו חומר תאפלוניזציה מתחבר לחומר המיועד לתאפלוניזציה, ויוצר חומר תאפלוניזציה חדש. תהליך זה מתבצע באמצעות חומרים כימיים שונים, וניתן לבצעו גם בתנאים של חום וגם בתנאים של קור.

תאפלוניזציה

התהליך של תאפלוניזציה הוא תהליך כימי שבו חומר תאפלוניזציה מתחבר לחומר המיועד לתאפלוניזציה, ויוצר חומר תאפלוניזציה חדש. תהליך זה מתבצע באמצעות חומרים כימיים שונים, וניתן לבצעו גם בתנאים של חום וגם בתנאים של קור.

תאפלוניזציה